



TUBING BETWEEN THE BENDS MUST BE ORDER SEPERATLY

STRAIGHT TUBE CAN BE ADDED @ THIS LOCATION

3" DIAMETER RIGID TUBING SUPPLIED BY OTHERS

PVC 20" RADIUS BEND WITH 3" NIPPLE SUPPLIED WITH SYSTEM

NOTE: FOR RUNS OVER 300 FT. A LONG RUN TIMER IS REQUIRED. MAXIMUM RUN LENGHT IS 1500 FT.

TWD SIDED END STATION AS SHOWN ON DRAWING 99-920

TWD SIDED END STATION AS SHOWN ON DRAWING 99-920

NOTE: TURBINE AND CONTROL BOX MAY BE REMDTELY LOCATED IN UTILITY CLOSET , MECHANICAL ROOM, ETC.

AIRFLOW CONTROL VALVE P/N B5471 (2 REQD)

TURBINE UNIT P/N B5470

ELECTRICAL CONTROLS P/N 99-876

120V 60HZ 20 AMP OUTLET

38 1/2" TYPICAL

HAMILTON AIR

MODEL HT-19 PNEUMATIC TRANSPORT SYSTEM with DOUBLE SIDED TELLERS AT BOTH ENDS (HT19-DDT)