est. 1967

HAMILTON CUSTOM MADE SECURITY







Custom built to your specifications for superior security







est. 1967

HAMILTON

CUSTOM MADE SECURITY

Built to Your Specifications

Choose virtually any combination of interiors, sizes, and color













POPULAR INTERIOR OPTIONS









TRTL-30



These high-security safes are rated to substantially resist mechanical and high-temperature attacks.





- TWO-HOUR FIRE RATING
- UL LISTED FOR 30-MINUTE ATTACK WITH TOOL AND TORCH
- LATEST IN COMPOSITE TECHNOLOGY

TWO-HOUR FIRE RATING

- MECHANICAL RELOCKERS
- 5" DOOR
- 31/2" COMPOSITE BODY
- CUSTOM BUILT FOR YOUR NEEDS



STEEL SAFES





Versatile Hamilton steel safes allow you to configure security storage to fit virtually any need.





SECURITY RATINGS: TL-15 AND TL-30 BODY: 1" OR EQUIVALENT STEEL PLATE

DOOR: TL-15 = 1" TL-30 = 2"

BOLTWORK:

- SOLID STEEL BOLTS
- MECHANICAL RELOCKER INCLUDED TO PROVIDE A SECONDARY DEFENSE

TYPES:

TELLER | TELLER RECEIVERS | DEPOSITORIES SQUARE SAFE | PORTABLE VAULTS

COMPOSITE SAFES





An alternate to plate steel, composite safes have a body & door that consist of thin steel forms filled with high-performance, high-tech aggregate.



\bigcirc

TWO-HOUR FIRE RATING

SECURITY RATINGS:

- TL-15, TL-30, TL-30X6
- 2-HOUR FIRE RATING

BODY:

- 2" COMPOSITE FOR TL-15 AND TL-30
- 4" COMPOSITE FOR TL-30X6

DOOR: TL-15 = 2" | TL-30 = 4"

BOLTWORK:

- SOLID STEEL BOLTS
- MECHANICAL RELOCKER INCLUDED TO PROVIDE A SECONDARY DEFENSE

YPES:

TELLER SAFE | TELLER RECEIVERS DEPOSITORIES | SQUARE SAFE PORTABLE VAULTS

TRTL-30x6





"The ultimate in high security," Hamilton manufactures safes that are UL rated to withstand 30-minute attacks using both torch (TR) and tools (TL).





TWO-HOUR FIRE RATING

- UL LISTED 30-MINUTE TORCH AND TOOL ATTACK ON ALL SIX SIDES OF THE SAFE.
- THE LATEST COMPOSITE TECHNOLOGY
- MASSIVE 4-WAY BOLTWORK
- GLASS RELOCKERS
- PERFECT FOR JEWELERS, BANKS, CREDIT UNIONS AND PHARMACEUTICAL STORAGE