

UL Listed Class M "Milford"







est. 1967



CUSTOM MADE SECURITY


"Milford" Vault Door (HUD-M-3680)

Hamilton Fire Door delivers maximum security with architectural appeal. Available in UL-Listed Class M, Hamilton's door is tough, reliable and loaded with many features. The Door is engineered to provide superior protection against forced entry and fire. Using a Hybrid frame and door made up of steel and high strength concrete barrier. This is a great option for commercial industry, cannabis and residential storm shelter.



Emergency Release Mechanism

51.500 [1308]



OPTIONAL

- Custom door sizes
- Day gate options
- Access Control
- Electric Strike
- Closer
- Timelock
- High Security Electronic locks
- Door Buck frame
- Colors: Black, Parchment, Gray Leatherette, Instrument Tan

The Hamilton's HUD-M-RS3680 vault door and frame assembly met the requirements of UL 10C, UL 10B and ULC S104 for a 3-hour fire-resistance rating with hose stream. The Class M rating is 15 minute UL Security test. UL is conducting the Ballistic testing. We are also having the door acoustic rated STC 50 to 60. (Sound transmission class)

INNOVATIVE DESIGN BENEFITS

- STANDARD DOOR CAN BE CUSTOMIZED TO SPECIAL HEIGHT/WIDTH REQUIREMENTS
- LIFE SAFETY FEATURES DESIGNED INTO VALUE DOOR
- EXTRA LAYER OF SECURITY WITH BUILT-IN DEADMAN
- RIGID VAULT DOOR FRAME AND TRIM ALLOWS FOR EASY GROUTLESS INSTAL-LATION AND COVERS THE COMPLETE OPENING

FEATURES

- LOW MAINTENANCE STAINLESS AND PAINTED CHARCOAL GRAY CONSTRUCTION
- UL LISTED CLASS M
- STANDARD SIZE: 36" X 80" C.O.
- MASONRY OPENING 50"W X 87 1/2" H
- STANDARD 4-WHEEL COMBINATION LOCK
- FIVE POINT LOCKING SYSTEM
- EMERGENCY RELEASE MECHANISM
- HEAT SENSOR AND DOOR CONTACT
- RIGHT OR LEFT SWING
- MECHANICAL AND THERMAL RE-LOCKERS
- 3-HOUR FIRE
- UL LISTED DRILL RESISTANT HARD PLATE

A GUNNEBO° COMPANY





854[1063]

